



型号 (Model)		PA2610 36V/10A
额定输入电压 (Rated input voltage)		AC 220V/110V±5%
额定输出电压 (Rated output voltage)		0~36V
额定输出电流 (Rated output current)		0~10A
变压方式 (Variable Pressure way)		线性电源
负载调节率 (Effect of load)	电压 (Voltage)	<0.02%+3mV
	电流 (Current)	<0.02%+3mA
电源调节率 (Power regulation)	电压 (Voltage)	<0.02%+3mV
	电流 (Current)	<0.02%+3mA
设定值解析度 (Set value resolution)	电压 (Voltage)	10mV
	电流 (Current)	1mA
设定值精度 (Precision of set value)	电压 (Voltage)	≤0.02%+2字节
	电流 (Current)	≤0.02%+2字节
回读值解析度 (returnread value resolution)	电压 (Voltage)	10mV
	电流 (Current)	1mA
回读值精度 (Return accuracy)	电压 (Voltage)	≤0.2%+2字节
	电流 (Current)	≤0.2%±6mA
温度 (Temperature)	操作环境 (Operating environment)	0 to 40℃ ≤85R. H.
	储存环境 (Storage environment)	-15 to 70℃ ≤85R. H
尺寸 Dimension (WxHxD(mm))		214x108x365
包装重量 (净重) (Weight)		6.2Kg

1

PA2600系列是新一代高品质可编程直流电源,兼具桌上型和系统型的特性,可任意搭配其他仪器,集成为特殊功能的测试系统,以完成不同场合下的测量需求,可通过面板键盘编辑程序,给用户的使用带来极大的方便,是普通可编程电源的换代产品,具有极高的性价比优势。



PA2600系列可编程直流电源,支持SCPI通信协议。SCPI是一种用于可编程仪表的标准命令,它定义了一套通讯时的命令规则。用于PA2600系列电源的命令分成两大类:基本命令(IEEE-488.2公用命令集)和PA2600系列指定的命令集。

2

3

可以进行远程操作,将电源与主机相连,编程量测命令,读取电源的电流输出值;拥有丰富功能按键,可以按照设置自己所需测量条件,方便操作。



应用领域 Application field

1. 电子产品开发
2. 器件测试
3. 通信行业
4. 实验室和科研机构

PINTECH品致官网: www.pintech.com.cn

中国地区免费热线: 400-628-7588
800-716-7789



微信公众号



官网



京东商城