

GOTECH "the best partner" to raise your competition

GT-7049-1 永久壓縮歪度測試器

Compression And Deformation Tester

CNS 3560 圖1(2)、JIS K6262:2013 圖1(a)、ASTM D395-2018 方法B、ISO 815-1:2014 圖1(a)、GB/T 7759.1-2015 圖1(a)

本器用於橡膠靜態壓縮試驗。取標準試片，夾於本器平面板之間，以螺絲旋轉，壓縮至一定比率，再放進一定溫度之烘箱（另購）中，經規定之時間後取出，拆下試片，冷卻30分鐘，測其厚度，代入公式求其壓縮歪度。

It's used especially to test the static compression for rubber.
Place one standard specimen between parallel flat plates,
revolve the screws then compress it a certain range of percent-
age and then put into the oven under the specified temperature
for a certain time period then take it off cooling for 30 minutes
to measure its thickness for calculating its permanent
deformation rate.



GT-7049-1



GT-7049-1H

型號 Model	GT-7049-1	GT-7049-1H
樣式 Type	方形，四柱式	
測試器可承受溫度範圍 Operating temperature	-70°C ~ 100°C	常溫 Ambient temp. ~ 300°C
間隔板規格 Size of compression plate(W×D)	240mm×145mm	
體積 Dimension(W×D×H)	240×145×150mm	

瞭解更多產品信息，請登錄我司網站 www.gotech.biz