



**HV Inline valve, DN 16 ISO-KF,
pneumatic, SS/FKM, "A"-dim.
102 mm**






HV Inline valve, DN 16 ISO-KF, pneumatic, SS/FKM, "A"-dim. 102 mm

- Single acting, normally closed (air to open / spring to close)
- With elastomer seals for high vacuum operation
- Additional bellows segments increase the service life
- Can be operated in any orientation
- Additional O-ring materials available

Dimensions



A	102 mm
B	110 mm
C	57 mm

Technical Data

	HV Inline valve, DN 16 ISO-KF, pneumatic, SS/FKM, "A"-dim. 102 mm
Feedthrough	Bellows Stainless steel
Seal	FKM
Type	HV Inline Valve
Temperature range	-20 – 150 °C
Housing	Stainless steel
Actuator	Pneumatic
Tightness	$1 \cdot 10^{-11}$ Pa m ³ /s $1.33 \cdot 10^{-9}$ Torr l/s $1 \cdot 10^{-9}$ mbar l/s
Conductance value with molecular flow	4 l/s
Operating pressure min.	$1 \cdot 10^{-8}$ hPa $7.5 \cdot 10^{-9}$ Torr $1 \cdot 10^{-8}$ mbar
Pressure max. (absolute)	1,000 hPa 750 Torr 1,000 mbar
Bakeout temperature: actuator, pilot valve	60 °C 140 K -213.15 °F
Bakeout temperature: housing	150 °C 302 K -123.2 °F
Differential pressure in closing direction	1,400 hPa 1,050 Torr 1,400 mbar
Differential pressure in opening direction	1,400 hPa 1,050 Torr 1,400 mbar
Weight	1 kg 2.2 lb
Compressed air volume	10 cm ³
Connection flange	DN 16 ISO-KF
Closing/opening time	1.25 s/1.5 s
Compressed air (overpressure)	6 000 – 8 000 hPa

Order number

	HV Inline valve, DN 16 ISO-KF, pneumatic, SS/FKM, "A"-dim. 102 mm
HV Inline valve, DN 16 ISO-KF, pneumatic, SS/FKM, "A"-dim. 102 mm	AIVP-S02100

Your Success. Our Passion.

We give our best for you every day –
worldwide!

Are you looking for an optimum vacuum solution?

Talk to us:

Pfeiffer Vacuum GmbH

Germany

T +49 6441 802-0

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 7/5/2024

Follow Us On Social Media
#pfeiffervacuum



PFEIFFER  **VACUUM**

www.pfeiffer-vacuum.com