





HV Inline valve, DN 25 ISO-KF, pneumatic, SS/FKM, "A"-dim. 107 mm





A 107 mm
B 108 mm
C 57 mm


HV Inline valve



HV Inline valve, DN 25 ISO-KF, pneumatic, SS/FKM, "A"-dim. 107 mm

- Single acting, normally closed (air to open / spring to close)
- With elastomer seals for high vacuum operation
- Additional bellows segments increase the service life
- Can be operated in any orientation
- Additional O-ring materials available

Dimensions



PFEIFFER VACUUM

HV Inline valve

Technical Data	HV Inline valve, DN 25 ISO-KF, pneumatic, SS/FKM, "A"-dim. 107 mm
Feedthrough	Bellows Stainless steel
Seal	FKM
Туре	HV Inline Valve
Temperature range	-20 – 150 °C
Housing	Stainless steel
Actuator	Pneumatic
Tightness	1 · 10 ⁻¹¹ Pa m ³ 1.33 · 10 ⁻⁹ 1 · 10 ⁻⁹ /s Torr l/s mbar l/s
Conductance value with molecular flow	9 l/s
Operating pressure min.	1 · 10 ⁻⁸ hPa 7.5 · 10 ⁻⁹ Torr 1 · 10 ⁻⁸ mbar
Pressure max. (absolute)	1,000 hPa 750 Torr 1,000 mbar
Bakeout temperature: actuator, pilot valve	60 °C 140 K -213.15 °F
Bakeout temperature: housing	150 °C 302 K -123.2 °F
Differential pressure in closing direction	1,400 hPa 1,050 Torr 1,400 mbar
Differential pressure in opening direction	1,400 hPa 1,050 Torr 1,400 mbar
Weight	1.5 kg 3.31 lb
Compressed air volume	10 cm ³
Connection flange	DN 25 ISO-KF
Closing/opening time	1.25 s/1.5 s
Compressed air (overpressure)	6 000 – 8 000 hPa

Order number	HV Inline valve, DN 25 ISO-KF, pneumatic, SS/FKM, "A"-dim. 107 mm
HV Inline valve, DN 25 ISO-KF, pneumatic, SS/FKM, "A"-dim. 107 mm	AIVP-S03100



Your Success. Our Passion.

We give our best for you every day worldwide!



Are you looking for an optimum vacuum solution? Talk to us:

Pfeiffer Vacuum GmbH Germany T+49 6441 802-0

Or scan the barcode, to visit our web page:



https://webportal.pfeiffer-vacuum.com/global/en/contact



Follow Us On Social Media #pfeiffervacuum















www.pfeiffer-vacuum.com