





RME 005 A, Gas regulating valve, solenoid actuated, control range from 0.085 to 8.5 hPa I/s




RME 005 A



RME 005 A, Gas regulating valve, solenoid actuated, control range from 0.085 to 8.5 hPa l/s


- Two connections and a connection cable required as accessories
- Drive: Solenoid
- Regulating range from 0.085 to 8.5 hPa l/s
- Normally closed (n. c.)

Characteristics



PFEIFFER VACUUM

Dimensions



RME 005 A

Technical Data	RME 005 A, Gas regulating valve, solenoid actuated, control range from 0.085 to 8.5 hPa l/s
Gas flow min. controllable	8.5 · 10 ⁻² hPa·l/s
Gas flow max. controllable	8.5 · 10 ⁰ hPa·l/s
Duty cycle	100 %
Supply: Power consumption max.	2.5 W
Control voltage	0 – 24 V DC
Seal	FKM
Туре	Gas control valve
Ambient temperature	5 – 50 °C
Housing	Stainless steel
Mounting orientation	Arbitrary
Actuator	Electromagnetic
Control	RVC 300
Tightness	1 · 10 ⁻¹⁰ Pa m ³ 1.33 · 10 ⁻⁸ 1 · 10 ⁻⁸ /s Torr l/s mbar l/s
Pressure max.	2,000 hPa 1,500 Torr 2,000 mbar
Min. controllable gas flow	8.5 · 10 ⁻² hPa·l/s
Max. controllable gas flow	8.5 · 10 ⁰ hPa·l/s
Bakeout temperature: actuator, de-energized	80 °C 176 K -193.2 °F
Pressure min.	1 · 10 ⁻⁸ hPa <mark> </mark> 7.5 · 10 ⁻⁹ Torr <mark> </mark> 1 · 10 ⁻⁸ mbar
Weight	96 g
Pressure max.	2,000 hPa
Response time	30 ms
Power consumption max.	2.5 W
Connection flange	DN 5 mm M14x1 Thread
Weight	96 g

Order number	RME 005 A, Gas regulating valve, solenoid actuated, control range from 0.085 to 8.5 hPa l/s
RME 005 A, Gas regulating valve, solenoid actuated, control range from 0.085 to 8.5 hPa l/s	PF I13 933



Your Success. Our Passion.

We give our best for you every day worldwide!



Are you looking for an optimum vacuum solution? Talk to us: Pfeiffer Vacuum Components & Solutions GmbH Germany T+49 551 99963-0 info-cs@pfeiffer-vacuum.com Or scan the barcode, to visit our web page:



https://webportal.pfeiffer-vacuum.com/global/en/contact



Follow Us On Social Media #pfeiffervacuum













